

item number	A (mm)	thickness of metal sheet (mm)	weight (kg/pc)
<b>DZNP 100_VS</b>	250	2,0	0,21
<b>DZNP 150_VS</b>	300	2,0	0,25
<b>DZNP 200_VS</b>	350	2,0	0,39
<b>DZNP 300_VS</b>	450	2,0	0,50
<b>DZNP 400_VS</b>	550	2,0	0,63
<b>DZNP 500_VS</b>	650	2,0	0,71
<b>DZNP 600_VS</b>	750	2,0	0,82



**product description:** The load bearing profile is designed for fastening of the wire trays from ceiling together with a 2 threaded rods  $\varnothing$  8 mm, nuts M 8 and washers PD 8.

The wire tray is placed on the load bearing profile in the prepared cut-outs.

**surface finish:** VS - Pre-Galvanized according to EN 10346, EN 10143, zinc-layer 15-27  $\mu$ m

**meets the requirements:** EN 61537:02

**classification:** ČSN 73 0895 P 90-R  
 DIN 4102-12 E 90  
 STN 92 0205 PS 90  
 Fire classification depends on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.  
 Products are approved for non-standard constructions.

**storage:** ČSN EN 60721-3-1

