



product description: The anchors serve for the attaching of construction elements to the base material (concrete, stone).

configuration: IX - stainless steel AISI 316

sales amount: á 1 pc

storage: EN 60721-3-1

classification : ČSN 73 0895 P 90-R  
 DIN 4102-12 E 90  
 STN 92 0205 PS 90

Fire classification depends on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire

products are approved for non-standard constructions

item number	configuration	A	B	C anchor depth	D max. thickness of the material being attached	E min.depth of the drilled hole	thread
<b>INOXKPO 8X75</b>	<b>IX</b>	8	75	44	10	65	M8x25
<b>INOXKPO 10X95</b>	<b>IX</b>	10	95	48	20	70	M10x30

**approved loads of anchors in non-cracked concrete**

item number	limit load, tensile (kN)	limit load, shear (kN)	approved tensile load (kN)					approved loads, shear (kN)	
	C25/30	C25/30	C20/25	C25/30	C30/37	C40/50	C50/60	C20/25	C25/30
<b>INOXKPO 8X75</b>	19,6	19,5	5,7	6,3	7,0	8,1	8,6	6,9	6,9
<b>INOXKPO 10X95</b>	23,1	31,9	7,6	8,4	9,3	10,7	11,8	8,0	8,8