

DATA SHEET

coupling for corrugated pipes KOPOFLEX® and KOPODUR®
and doublecoated corrugated drainage pipes DUODREN



product description: slip-over coupling is intended to connect the corrugated pipes KOPOFLEX® or KOPODUR® and for connection of DUODREN drainage pipes
when using a sealing ring, the protection class is IP 67

material: PE

halogen-free: yes

self-snuffing: no

thermal resistance: -45 - +60 °C

fire class for underlying material: A1

UV stable: yes

protection types: IP 40 (when using a sealing ring IP 67)

meets the requirements: EN 61386-24:11, EN 61386-1 ed.2:09

storage: ČSN 64 0090

recycling codes:



coupling



bag



raschel bag

chemical resistance: YES: acetone, ammonia 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
NO: aniline, chlorinated hydrocarbons, tetrachlorocarbon

item number	outer Ø pipe (mm)	for pipes	fuses
02040_FA	40	KF 09040; KD 09040	●
02050_FA	50	KF 09050; KD 09050	●
02063_FA	63	KF 09063; KD 09063; DUODREN 63	
02075_FA	75	KF 09075; KD 09075; DUODREN 75	
02090_FA	90	KF 09090; KD 09090; DUODREN 90	●
02110_FA	110	KF 09110; KD 09110; DUODREN 110	
02125_FA	125	KF 09125; KD 09125	●
02160_FA	160	KF 09160; KD 09160	
02200_FB	200	KF 09200; KD 09200	